

Nh3 Ammonia Cracker Furnace Heat Treatment Bright Annealing For Cooper Pipelines

Our Product Introduction

Basic Information

- Place of Origin: SUZHOU, CHINA
- Brand Name: SUMAIRUI GAS
- Certification: CE, ISO9001, SGS, TUV
- Model Number: OSA-50
- Minimum Order Quantity: 1 set
- Price: Negotiable
- Packaging Details: Exporting wooden case /Film packing
- Delivery Time: 30-45 days
- Payment Terms: L/C, T/T, Western Union, MoneyGram
- Supply Ability: 100 sets/months



Product Specification

- Capacity: 300-350 Nm3/hr
- Material: Stainless Steel
- Reactor: Inconel 600
- Certificates: CE, ISO, ASME, GOST, KGS, NB Etc
- Color: Silver
- Application: Industrial
- Operation Mode: Fully Automatic
- Driving Type: Electrical
- Working Mode: Fully Automatic, 24 Hrs Non-stop
- Heating Time: 5-10min
- Noise Level: ≤50dB
- Product Name: Ammonia Cracker
- Safety Protection: Yes
- Temperature Range: 50-200°C
- Voltage: 220V

for more products please visit us on n2-nitrogengenerator.com

Product Description

Ammonia cracker for the heat treatment furnace bright annealing process for the cooper pipelines with ISO9001

Working Principal of Ammonia Cracker Unit

Cracker Unit is a vertical rectangular cross section furnace. It has ceramic blanket insulation lining on the walls and on the top. Floor of furnace is refractory bricks lined. In this furnace retort is suspended from the top. The retort is made of 20% - 25% Chrome / Nickel seamless tubes. This material is suitable up to 1100° C temp. and safe for operating temperature for around 850 deg. C. (maximum). The retort is centrifugal casted having thickness of around 10 mm. On the side wall of the furnace coil type Ni-chrome heating elements are provided refractory supports.

Temperature of the furnace box is controlled at 850° C. which in turn gives catalyst bed temperature inside the tubes of around 800°C. Temperature controllers are twin point type. Lower temperature set point shall be at 800° C. to give alarm in case furnace temperature falls during normal operation. Upper set point would switch on and switch off heaters automatically to maintain furnace temperature at 850° C. Heating elements are equally distributed through out the furnace height and all catalyst tubes are uniformly heated on all sides. Furnaces has ceramic fibers lining and outside furnace wall temperature shall be maximum 60° C.

Advantages of Ammonia Cracker Unit

On-site Ammonia cracking Unit to get Cracked Ammonia
It is economical Process to get Cracked Ammonia
It is easy to operate and less maintenance
Less space required



Suzhou Sumairui Gas System Co.,Ltd.



+8613812659092



dylan@sumairui.com



n2-nitrogengenerator.com

