

Air Compressor Heated Desiccant Air Dryer Twin Tower Screwing Centrifugal 80m3/Min

Our Product Introduction

Basic Information

- Place of Origin: SUZHOU, CHINA
- Brand Name: SUMAIRUI GAS
- Certification: ISO9001, CE, BV, SGS, TUV, ASME, GOST,NB,NR ETC
- Model Number: OSD-M
- Minimum Order Quantity: 1 set
- Price: Negotiable
- Packaging Details: Exporting wooden case /Film packing
- Delivery Time: 30-45 days
- Payment Terms: L/C, T/T, Western Union, MoneyGram
- Supply Ability: 100 sets/months



Product Specification

- Certificates: CE & ASME
- Material: Stainless Steel
- Flow: 5-20000 Nm3/hr
- Regeneration Gas Consumption: <7%
- Power Supply: 380-460V/50 Hz/60Hz
- Regeneration: 2-6 H
- Inlet Oil Content: <0.1ppm
- Pressure Loss: <0.5 Bar
- Dew Point: Available Customized
- Control Type: Siemens PLC
- Structure: Two Vertical Towers
- Controls: Digital
- Desiccant Type: AL2O3
- Dew Point: -40°F

for more products please visit us on n2-nitrogengenerator.com

Product Description**80 m³/min twin heated desiccant air dryer for the factory compressed station screwing/Centrifugal air compressor Heated Desiccant Air Dryer****Working condition and technical data**

Maximum inlet air temperature: 45°C
 Pressure range: 0.5-1.0Mpa
 Pressure dew point: -20°C ~ -40°C
 Inlet oil content: ≤0.1PPm
 Regeneration gas consumption: ≤7%
 Control mode: microcomputer automatic control / PLC control
 Power supply: 1-6nm 3 / min, AC 220 V / 50 Hz
 AC 380 V / 220 V / 50 Hz for 8nm 3 / min and above
 Period: T = 2-6 (H)
 Design condition: inlet temperature: 38 °C
 Ambient temperature: 38 °C
 Working pressure: 0.7MPa
 Pressure loss: ≤ 3% of design pressure
 Note: other special requirements are welcome to customize.

Characteristics of micro heat regeneration adsorption dryer

2-6 hours standard cycle;
 The pressure dew point can reach - 20 °C to - 40 °C;
 The regeneration gas consumption is less than 7%;
 High quality switching valve, stable and reliable, can ensure the integrity of the working process and prolong the working life of components;
 The activated alumina with high hygroscopicity is selected with uniform shape and size, high strength, low dew point, less dust and long service life;
 The unique regeneration pipeline design is adopted to ensure that the regeneration gas can be evenly distributed when the regeneration gas is heated and cooled, so that the adsorbent in the center of the adsorption tower is heated evenly, the heat dissipation is fast, and the regeneration is complete;
 The heater has reasonable design, good dehumidification and regeneration effect, low air consumption, high heating efficiency, and greatly reduces energy consumption;
 Programmable microcomputer controller, cycle time, adsorption, regeneration working time, heating time, heating temperature can be adjusted to achieve your satisfactory dew point value.

2.

Operating Conditions
 Inlet temperature: ≤38°C
 Ambient temperature: 1-45°C
 Standard Working Pressure: 0.7Mpa
 Power: AC 380-460 V/3P/50Hz/60Hz
 Standard Configuration
 PDP: -40°C
 Adsorbent life: 3 years
 Valve with Stainless Steel Core
 PLC Control
 Optional Configuration
 PDP: -70°C
 Dew point display and energy saving module
 Communication telex function
 High temperature and high pressure intake
 Galvanized or stainless steel pipe
 Tower insulation



Suzhou Sumairui Gas System Co.,Ltd.



+8613812659092



dylan@sumairui.com



n2-nitrogengenerator.com

No 161,ZhongfengJie, Suzhou High technology district, Suzhou