

SUZHOU, CHINA

GOST,NB,NR ETC

OSD-F

Negotiable

30-45 days

100 sets/months

1 set

ISO9001, CE, BV, SGS, TUV, ASME,

Exporting wooden case /Film packing

L/C, T/T, Western Union, MoneyGram

Ammonia NH3 Dryer 100Nm3/Hr 110PSIG Fully Automatic Control System HMI Furnace

Basic Information

- Place of Origin:
- Brand Name: SUMAIRUI GAS
- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:
- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:



Product Specification

 Material: 	Stainless Steel
• Flow:	10-10000 Nm3/hr
Pressure:	7-10 Bar
Dew Point:	-70°C
Certificates:	ISO, ASME, CE
 Application: 	Heat Treatment, Oil Refinery
Pipeline:	Seamless Steel
Flow Meter:	Included
Manometer:	Included
 Hydrogen Analyzer: 	Included
• HMI:	7 Inches/customized
PLC Control:	Siemens
• Ex-proof:	Customized
Highlight:	Ammonia NH3 Dryer, NH3 Dryer 100Nm3/hr, NH3 Ammonia Dryer

Our Product Introduction

Electron filed 100Nm3/hr 110 PSIG ammonia dryer with fully automatic control system HMI for Multi-purpose furnace

Liquid ammonia adsorbing dryer device

Liquid ammonia dryer working principle :

This ammonia dryer adopt absorbing technology. The raw material come form Liquid ammonia storage system, enter into dryer, will be adsorbed by 3A molecular sieves inside dryers, therefore to get pure &clean ammonia dew point lower than -40°C. Because the molecular sieves will saturation after period of time, so we molecular sieves must regenerate, while regeneration the molecular sieves temperature should beyond 250°C, meanwhile inlet some nitrogen, which make molecular sieves moisture will be take away by regenerate gas, regenerate molecular sieves can recycling using after cooling. Purification package adsorbing dryer insist of two adsorbers, pneumatic valve, solenoid valve, two adsorbers fully automatic control&switch, while one working another standby.

Dryers temperature control part make up of thermocouple, temperature

controller, contractor etc. Each adsorber will have one thermocouple, it located in the vessel middle position. Adsorber 2 thermcouple will share one temperature controller, via auxiliary relay to switch, dryer only heating control temperature when regenerate, the equipment heating temperature can set in temperature controller.

In order to prevent liquid ammonia freeze in winter Spaying device Should be using in former,hot water provide by hot water gasification system,heater make water hot,spraying ammonia cylinder,spaying water enter into water pool,via pump pressurize recycling heating,spaying. This device regenerate gas-Nitrogen



Application:

1. Metallurgy: For anneal protection, agglomeration protection, furnace washing and blowing ,etc. Used in fields such as metal heating treatment, powder metallurgy, magnetic material,copper process, metallic mesh, galvanized wire, semiconductor, etc. 2. Chemical and new material industries: For chemical material gas, pipeline blowing, gas replacement, gas protection, product transport, etc. Used in fields such as chemical ,urethane elastic fiber, rubber, plastic, tyre, polyurethane, biological technology, intermediate, etc.

3. Electronic industry: For encapsulation, agglomeration, anneal, deoxygenation, storage of electronic products. Used in fields such as peak welding, circumfluence welding, crystal, piezoelectricity, electronic porcelain, electronic copper tape, battery, electronic alloy material, etc.

4.Food, Beverage, Cereal & Drug Industries: It's suitable to use in gas-adjusting package and nitrogen package of fruits, vegetables, flowers, tea leaves and puffed food, custard pie, milk bread, European-style egg roll, various cookies, farm products and local special products, such as rice, seed and chestnut, also kinds of drugs etc.

