

Suzhou Sumairui Gas System Co., Ltd.

SUZHOU, CHINA

GOST,NB,NR ETC

OSD-F

Negotiable

30-45 days

100 sets/months

1 set

ISO9001, CE, BV, SGS, TUV, ASME,

Exporting wooden case /Film packing

L/C, T/T, Western Union, MoneyGram

Basic Information

- Place of Origin:
- Brand Name: SUMAIRUI GAS

n2-nitrogengenerator.com

- Certification:
- Model Number:
- Minimum Order Quantity:
- Price:

SUMAIRUI

- Packaging Details:
- Delivery Time:
- Payment Terms:
- Supply Ability:



Product Specification

Material:	Stainless Steel
• Flow:	10-10000 Nm3/hr
Pressure:	7-10 Bar
Dew Point:	-70°C
Certificates:	ISO, ASME, CE
Application:	Heat Treatment, Oil Refinery
Pipeline:	Seamless Steel
• Flow Meter:	Included
Manometer:	Included
Hydrogen Analyzer:	Included
• HMI:	7 Inches/customized
PLC Control:	Siemens
• Ex-proof:	Customized
Highlight:	Compressed, ammonia dryer Chemical, dry ammonia

Chemical products using ammonia dryer to improve efficiency & quality verified by CE cetificates

Liquid ammonia adsorbing dryer device

Liquid ammonia dryer working principle :

This ammonia dryer adopt absorbing technology. The raw material come form Liquid ammonia storage system, enter into dryer, will be adsorbed by 3A molecular sieves inside dryers, therefore to get pure &clean ammonia dew point lower than -40°C. Because the molecular sieves will saturation after period of time, so we molecular sieves must regenerate, while regeneration the molecular sieves temperature should beyond 250°C, meanwhile inlet some nitrogen, which make molecular sieves moisture will be take away by regenerate gas, regenerate molecular sieves can recycling using after cooling. Purification package adsorbing dryer insist of two adsorbers, pneumatic valve, solenoid valve, two adsorbers fully automatic control&switch, while one working another standby.

Dryers temperature control part make up of thermocouple, temperature

controller,contractor etc.Each adsorber will have one thermocouple,it located in the vessel middle position.Adsorber 2 thermcouple will share one temperature controller,via auxiliary relay to switch,dryer only heating control temperature when regenerate, the equipment heating temperature can set in temperature controller.

In order to prevent liquid ammonia freeze in winter Spaying device

Should be using in former,hot water provide by hot water gasification system,heater make water hot,spraying ammonia cylinder,spaying water enter into water pool,via pump pressurize recycling heating,spaying. This device regenerate gas-Nitrogen



Application:

1. Metallurgy: For anneal protection, agglomeration protection, furnace washing and blowing ,etc. Used in fields such as metal heating treatment, powder metallurgy, magnetic material,copper process, metallic mesh, galvanized wire, semiconductor, etc. 2. Chemical and new material industries: For chemical material gas, pipeline blowing, gas replacement, gas protection, product transport, etc. Used in fields such as chemical ,urethane elastic fiber, rubber, plastic, tyre, polyurethane, biological technology, intermediate, etc.

3. Electronic industry: For encapsulation, agglomeration, anneal, deoxygenation, storage of electronic products. Used in fields such as peak welding, circumfluence welding, crystal, piezoelectricity, electronic porcelain, electronic copper tape, battery,

