

Instrument High Pressure Desiccant Air Dryer Heated Desiccant Dryer 2.5m3/Min 22 Bar

Our Product Introduction

Basic Information

- Place of Origin: SUZHOU, CHINA
- Brand Name: SUMAIRUI GAS
- Certification: ISO9001, CE, BV, SGS, TUV, ASME, GOST,NB,NR ETC
- Model Number: OSD-M
- Minimum Order Quantity: 1 set
- Price: Negotiable
- Packaging Details: Exporting wooden case /Film packing
- Delivery Time: 30-45 days
- Payment Terms: L/C, T/T, Western Union, MoneyGram
- Supply Ability: 100 sets/months



Product Specification

- Certificates: CE & ASME
- Material: Stainless Steel
- Flow: 5-20000 Nm3/hr
- Regeneration Gas Consumption: 7%
- Power Supply: 380-460V/50 Hz/60Hz
- Regeneration: 2-6 H
- Inlet Oil Content: 0.1ppm
- Pressure Loss: 0.5 Bar
- Dew Point: Available Customized
- Control Type: Siemens PLC
- Structure: Two Vertical Towers
- Controls: Digital
- Desiccant Type: AL2O3
- Dew Point: -40°F

for more products please visit us on n2-nitrogengenerator.com

Product Description

2.5 m3/min 22 bar heated desiccant air dryer for laser cutting machine clean & white cutting

Heated Desiccant Air Dryer

Working condition and technical data

Maximum inlet air temperature: 45
 Pressure range: 0.5-1.0Mpa
 Pressure dew point: -20 ~ -40
 Inlet oil content: ≤0.1PPm
 Regeneration gas consumption: ≤7%
 Control mode: microcomputer automatic control / PLC control
 Power supply: 1-6nm 3 / min, AC 220 V / 50 Hz
 AC 380 V / 220 V / 50 Hz for 8nm 3 / min and above
 Period: T = 2-6 (H)
 Design condition: inlet temperature: 38
 Ambient temperature: 38
 Working pressure: 0.7MPa
 Pressure loss: ≤ 3% of design pressure
 Note: other special requirements are welcome to customize.

Characteristics of micro heat regeneration adsorption dryer

2-6 hours standard cycle;
 The pressure dew point can reach - 20 to - 40 ;
 The regeneration gas consumption is less than 7%;
 High quality switching valve, stable and reliable, can ensure the integrity of the working process and prolong the working life of components;
 The activated alumina with high hygroscopicity is selected with uniform shape and size, high strength, low dew point, less dust and long service life;
 The unique regeneration pipeline design is adopted to ensure that the regeneration gas can be evenly distributed when the regeneration gas is heated and cooled, so that the adsorbent in the center of the adsorption tower is heated evenly, the heat dissipation is fast, and the regeneration is complete;
 The heater has reasonable design, good dehumidification and regeneration effect, low air consumption, high heating efficiency, and greatly reduces energy consumption;
 Programmable microcomputer controller, cycle time, adsorption, regeneration working time, heating time, heating temperature can be adjusted to achieve your satisfactory dew point value.

2.

Operating Conditions

Inlet temperature: ≤38
 Ambient temperature: 1-45
 Standard Working Pressure: 0.7Mpa
 Power: AC 380-460 V/3P/50Hz/60Hz
 Standard Configuration

PDP: -40

Adsorbent life: 3 years

Valve with Stainless Steel Core

PLC Control

Optional Configuration

PDP: -70

Dew point display and energy saving module

Communication telex function

High temperature and high pressure intake

Galvanized or stainless steel pipe

Tower insulation



Suzhou Sumairui Gas System Co.,Ltd.



+8613812659092



dylan@sumairui.com



n2-nitrogengenerator.com

No 161,ZhongfengJie, Suzhou High technology district, Suzhou