

## System Ammonia Cracking Technology Nh3 Cracking H2 Generator For Industrial Furnaces

Our Product Introduction

### Basic Information

- Place of Origin: SUZHOU, CHINA
- Brand Name: SUMAIRUI GAS
- Certification: CE, ISO9001, SGS, TUV
- Model Number: OSA-50
- Minimum Order Quantity: 1 set
- Price: Negotiable
- Packaging Details: Exporting wooden case /Film packing
- Delivery Time: 30-45 days
- Payment Terms: L/C, T/T, Western Union, MoneyGram
- Supply Ability: 100 sets/months



### Product Specification

- Capacity: 300-350 Nm3/hr
- Material: Stainless Steel
- Reactor: Inconel 600
- Certificates: CE, ISO, ASME, GOST, KGS, NB Etc
- Color: Silver
- Application: Industrial
- Operation Mode: Fully Automatic
- Driving Type: Electrical
- Working Mode: Fully Automatic, 24 Hrs Non-stop
- Heating Time: 5-10min
- Noise Level: ≤50dB
- Product Name: Ammonia Cracker
- Safety Protection: Yes
- Temperature Range: 50-200
- Voltage: 220V

for more products please visit us on [n2-nitrogengenerator.com](http://n2-nitrogengenerator.com)

## Product Description

### -80 dew point Automatic Ammonia Crackers H2 Generator by Ammonia decomposition H2 Plant for Industrial furnaces

#### BASIC DESCRIPTION

Ammonia gas from cylinders passed over a bed of nickel catalyst at 850 temperature and cracking take place in two different gas i.e. 75% Hydrogen and 25% Nitrogen.

#### **$2\text{NH}_3 \rightarrow \text{N}_2 + 3\text{H}_2$ (IN PRESENCE OF NICKEL CATALYST AT 850 )**

Ammonia cracking is endothermic reaction and require heat from other source. The source is electrically heated/gas fired furnace (Rectangular Shape) and a retort made of heat resistance alloy is provided to hold the ammonia cracking catalyst. Cracked ammonia from furnace is cooled to ambient temperature in a shell & Tube type heat exchanger and having dew point around (-) 30 . Further product gas is passed through a molecular sieves filled Gas Purifier to achieve a dew point up to (-) 80

#### SALIENT FEATURES

Centrifugally cast retort  
Furnace skin temperature is 20  
Dew Point up to (-) 80  
Heating Element is Ni-Cr (80-20%)  
Long service cycle, Negligible maintenance, High turn down ratio  
Heavy duty operations for years and years  
Fully automatic no need of operator

#### APPLICATION

Heat Treatment Furnace for bright annealing  
Brazing Industry  
For Gas Purification System  
Stainless Steel Industry  
Power Sector

#### Major applications of Ammonia Cracker Unit

- I On site Generation of cracked gas Ammonia
- I For Nitrogen Generation Plants
- I Pipe Manufacturing Industry
- I Sintered Brazing Industry
- I Galvanizing Plants
- I Automobile Industry
- I Heat Treatments





**Suzhou Sumairui Gas System Co.,Ltd.**



+8613812659092



dylan@sumairui.com



n2-nitrogengenerator.com

No 161,ZhongfengJie, Suzhou High technology district, Suzhou