

Absorption Heatless Desiccant Air Dryer Twin Tower Dual Air Dryer N2 System Puring

Our Product Introduction

Basic Information

- Place of Origin: SUZHOU, CHINA
- Brand Name: SUMAIRUI GAS
- Certification: ISO9001, CE, BV, SGS, TUV, ASME, GOST,NB,NR ETC
- Model Number: OSD-P
- Minimum Order Quantity: 1 set
- Price: Negotiable
- Packaging Details: Exporting wooden case /Film packing
- Delivery Time: 15-25 days
- Payment Terms: L/C, T/T, Western Union, MoneyGram
- Supply Ability: 100 sets/months



Product Specification

- Maximum Inlet Air Temperature: 45
- Pressure: 0.5-1.6 Mpa
- Dew Point: Available Customized
- Material: Carbon Steel/Stainless Steel
- Regeneration Gas Consumption: $\leq 14\%$
- Power Supply: 110-230 V Available
- Cycle: 10 Min
- Pressure Loss: 0.5 Bar
- Certificates: CE/ASME/ISO
- Other Request: Available Customized
- Air FlowRate: 1000-3000CFM
- AirInlet Temperature: ≤ 45
- Air Quality: Class 1
- Control Mode: PLC

for more products please visit us on n2-nitrogengenerator.com

Product Description**Twin desiccant air dryer of heatless power free for air compression system /N2 system purging****Heatless Desiccant Air Dryer****Working condition and technical data**

Maximum inlet air temperature:45
 Pressure range:0.5-1.0Mpa
 Pressure dew point:-20 ~ -40
 Inlet oil content:≤0.1PPm
 Regeneration gas consumption:≤14%
 Control mode: microcomputer automatic control / PLC control
 Power Supply:AC 220V/50HZ
 cycle:T=10(min)
 Design condition: inlet temperature: 38
 Ambient temperature: 38
 Working pressure: 0.7MPa
 Pressure loss: ≤ 3% of design pressure

Features:

- 10 minutes cycle in the desiccant dryers.
- The pressure dew point of the desiccant dryers can reach - 20 to - 40 ;
- Regeneration gas consumption ≤ 14%;
- High-quality switching valve in the stable and reliable, can ensure the integrity of the working process, prolong the working life of components;
- The activated alumina with high hygroscopicity is selected in the Heatless Desiccant Air Dryer, with uniform shape and size, high strength, high dew point, less dust, and long service life;
- The amount of regeneration gas can be adjusted according to the operation load demand of the equipment to achieve energy-saving effect;
- Special airflow diffusion device and automatic regeneration in the desiccant dryers, ensure the service life of desiccant;
- Programmable microcomputer controller, adsorption, regeneration working time can be adjusted to achieve your satisfactory dew point value.

Note: other special requirements are welcome to customize.

2.Operating Conditions

Inlet temperature:≤38
 Ambient temperature:1-45
 Standard Working Pressure:0.7Mpa
 Power:AC220V/1P/50Hz/60Hz
 Standard Configuration
 PDP:-40
 Adsorbent life:3 years
 Valve with Stainless Steel Core
 PLC Control
 Optional Configuration
 PDP:-70
 Dew point display and energy saving module
 Communication telex function
 High temperature and high pressure intake
 Galvanized or stainless steel pipe
 Tower insulation



SUMAIRUI

Suzhou Sumairui Gas System Co.,Ltd.



+8613812659092



dylan@sumairui.com



n2-nitrogengenerator.com

No 161,ZhongfengJie, Suzhou High technology district, Suzhou