

Brewery Air Compressor Nitrogen Generator For Food Packaging

Basic Information

Place of Origin: SUZHOU, CHINABrand Name: SUMAIRUI GAS

• Certification: ISO9001, CE, BV, SGS, TUV, ASME,

GOST,NB,NR ETC

Model Number: OSP
Minimum Order Quantity: 1 set
Price: Negotiable

Packaging Details: Exporting wooden case /Film packing

Delivery Time: 30-45 days

Payment Terms:
 L/C, T/T, Western Union, MoneyGram

Supply Ability: 100 sets/months



Product Specification

Flow: 20-1000Nm3/hrPurity: 99.99%-99.999%

Dew Point: -80
Pressure: 5-200 Bar
Control Type: PLC Control

Instrument: Included
Mannometer: Included
Oxygen Analyzer: Included
Material: Stainless Steel

• Certificates: CE, ISO, ASME, GOST, KGS, NB Etc

Medium: Clean N2
Display: HMI
Alarming System: Included
Flow Meter: Included
Customized: Yes

Food industry CE/ASME/ISO stainless steel high purity with certificates N2 nitrogen generator

Our simple turnkey Pressure Swing Adsorption (PSA) type Nitrogen Generator provides a cost-effective means for on-site N2 gas generation. It is based on using the latest PSA technology and utilizes Carbon Molecular Sieve (CMS) to separate nitrogen from the other gases contained in air. The Nitrogen Generator uses two beds of CMS to separate compressed air into a high-pressure nitrogen product stream and low-pressure oxygen enriched waste stream. Typical feed air pressure is 110 psig/7.6 barg. Typical nitrogen product purity for our systems is 99%. Product flow rate for the same system will be higher with better nitrogen recovery if a higher oxygen content can be accepted in the nitrogen product. Systems are available with a product purity up to 99.999% nitrogen (10 ppmv oxygen).

Generators are supplied as complete systems, ready for hookup to a compressed air supply, including air filters and controls for automatic operation. Start up is at the flip of a switch and maintenance is limited to changing filters every three to twelve months. Each Nitrogen Generator comes pre-tested and fine tuned to meet the customer specified nitrogen flow rate and purity.

Our nitrogen generators have proven to be very popular and reliable for many applications. Having your own nitrogen generator is a hassle free, safer alternative to high-pressure nitrogen bottles or liquid nitrogen, and you will always have nitrogen available at a reduced cost.

The Benefits of an Onsite Nitrogen Generating System

Benefits compared to previous models

Higher quality materials Lower energy consumption Shorter lead time Longer N2 generator lifetime

How did we do it

Simplification – 80% less parts used in our production process Automation – state-of-the-art welding and bending robots Modular isolation – two standard size PSA pressure vessels for all capacities

Service and maintenance

A smaller power consumption requires a smaller compressor. As a result, you will not only save on energy but also on running/service costs of the compressor. Furthermore, the stainless-steel valves have a longer lifetime than brass.

Model of OSP High purity PSA nitrogen generator

Item	Nitrogen purity (Nm3/hr)							Dimensions	Weight
	95%	99%	99.5%	99.9%	99.99%	99.995%	99.999%	(L*W*H) mm	KG
OSP5	21	13	11	8	5	4.2	3	1100*600*1700	300
OSP10	38	29	25	15	10	7.5	6.1	1200*650*1800	
OSP20	80	56	52	32	20	16	14	1600*1000*220 0	ı
OSP40	160	116	105.2	67.2	40	34	28	1800*1000*220 0	l
OSP60	252	174	157.8	100.8	60	51	45	1900*1200*220 0	l
OSP80	339.2	232	211	132	80	70	62	2000*1200*240 0	l
OSP100	420	290	263	168	100	90		2100*1600*250 0	l
OSP150	630	435	394.5	252	150	135	120	2500*1800*260 0	l
OSP200	848	580	526	336	200	180	160	2800*1900*285 0	l
OSP250	1060	725	657.5	420	250	225	200	3100*2000*320 0	ı
OSP300	1270	870	780	500	300	260	240	3900*2600*340 0	ı
OSP400	1696	1160	1052	672	400	360	1	4500*3250*360 0	ı
OSP500	2120	1450	1300	840	500	450	400	4900*3600*380 0	l
OSP600	2540	1740	1578	1000	600	540	480	5300*3600*390 0	1
OSP800	3390	2320	2100	1340	800	720	ı	5600*3900*410 0	l
OSP1000	4240	2900	2630	1680	1000	900	800	5800*4000*450 0	11800

Design reference:

Compressed air inlet pressure 7.5 bar(g)/108 psi(g)
Air quality 1.4.1 according to ISO 8573-1:2010
Nitrogen outlet pressure 6 bar(g)/87psi(g)
Nitrogen quality 1.2.1 according to ISO 8573-1:2010.
Designed working temperature max 50
Dew point at Nitrogen outlet - 40

Notes:

OSP nitrogen generator max working pressure 10 bar(g)/145psi(g) Following request of PSA on-site nitrogen generator will be customized : Working pressure 10 bar(g)/145 psi(g) Dew point - 50 Plug and play Movable/containerized Other special requirements as per site conditions

Nitrogen Generator Applications

Here are the five most popular nitrogen generator applications in the industrial industry.

Food Packaging

Modified Atmosphere Packaging (MAP) with nitrogen and nitrogen-CO2 gas mixes are often used in the food packaging industry to preserve perishable items by preventing spoilage, ensuring freshness, maintaining flavour, and extending the product shelf life. Onsite nitrogen generation is highly beneficial in the food packaging industry to maintain a quality product. Food packagers can save hundreds of thousands of dollars by having an onsite system installed.

Beverage Storage, Transport, and Dispensing

Like the food industry, the beverage industry can also improve from having onsite nitrogen generating systems. These systems make it more efficient to transport beverages to end users such as juice packagers, vintners, breweries, and other manufacturers of beverage dispensing systems.

Laser Cutting

The success of a laser cutter depends on a lean and efficient shop, which is why it is highly beneficial to generate your own nitrogen onsite. If you are currently purchasing high-pressure cylinder gas, you can achieve incredible cost savings by switching to a local system. Bulk liquid nitrogen systems for laser cutting typically have purge losses of up to 20% of the gas you are purchasing. An onsite nitrogen generator will eliminate these costly purge losses.

Electronics Manufacturing and Soldering

Many solder applications require high-purity nitrogen to reduce dross on solder spots and reduce surface tension. High-purity nitrogen allows solder to cleanly breakaway from the solder site. Having an onsite nitrogen generating system is the most cost-effective way to meet your nitrogen requirements.

Fuel and Chemical Tank Inerting

The ideal inert gas for blanketing or purging fuel and chemical tanks is nitrogen. Having an onsite nitrogen system will reduce your costs and allow you to have a 24/7 nitrogen supply to meet your requirements.

Nitrogen Generator Services from SUMAIRUI GAS

Onsite nitrogen generators are extremely efficient and cost-effective for various industrial applications. By installing an onsite system, all you need to focus on is maintenance, while your investment pays for itself over time. We offer the following nitrogen generator services:

Maintenance Services

For help with installation, our team offers around-the-clock service support. If you require maintenance for your existing system, we will ensure that your nitrogen generator is running in great condition, so you can get back to your operations. For nearly three decades we have been helping our clients significantly reduce their industrial nitrogen and oxygen costs by utilizing leading-edge technologies such as onsite nitrogen and oxygen generating systems. We displace the requirement of having to purchase the gas. Instead, we sell our business clients the technology and equipment they need to make their own gas on site.





Suzhou Sumairui Gas System Co.,Ltd.

+8613812659092

dylan@sumairui.com

n2-nitrogengenerator.com

No 161, ZhongfengJie, Suzhou High technology district, Suzhou