

Air Compressor Heatless Desiccant Air Dryer For Clean Air Treatment System

Our Product Introduction

Basic Information

- Place of Origin: SUZHOU, CHINA
- Brand Name: SUMAIRUI GAS
- Certification: ISO9001, CE, BV, SGS, TUV, ASME, GOST,NB,NR ETC
- Model Number: OSD-P
- Minimum Order Quantity: 1 set
- Price: Negotiable
- Packaging Details: Exporting wooden case /Film packing
- Delivery Time: 15-25 days
- Payment Terms: L/C, T/T, Western Union, MoneyGram
- Supply Ability: 100 sets/months



Product Specification

- Maximum Inlet Air Temperature: 45°C
- Pressure: 0.5-1.6 Mpa
- Dew Point: Available Customized
- Material: Carbon Steel/Stainless Steel
- Regeneration Gas Consumption: ≤14%
- Power Supply: 110-230 V Available
- Cycle: 10 Min
- Pressure Loss: <0.5 Bar
- Certificates: CE/ASME/ISO
- Other Request: Available Customized
- Highlight: **air compressor Heatless desiccant air dryer, air compressor desiccant air dryer, heatless desiccant dryer**

for more products please visit us on n2-nitrogengenerator.com

CE/ASME verified OSD Hea-less desiccant air dryer for clean air treatment system

Heatless Desiccant Air Dryer

Working condition and technical data

Maximum inlet air temperature:45°C

Pressure range:0.5-1.0Mpa

Pressure dew point:-20°C ~ -40°C

Inlet oil content:≤0.1PPm

Regeneration gas consumption:≤14%

Control mode: microcomputer automatic control / PLC control

Power Supply:AC 220V/50HZ

cycle:T=10(min)

Design condition: inlet temperature: 38 °C

Ambient temperature: 38 °C

Working pressure: 0.7MPa

Pressure loss: ≤ 3% of design pressure

Features:

- 10 minutes cycle in the desiccant dryers.
- The pressure dew point of the desiccant dryers can reach - 20 °C to - 40 °C;
- Regeneration gas consumption ≤ 14%;
- High-quality switching valve in the stable and reliable, can ensure the integrity of the working process, prolong the working life of components;
- The activated alumina with high hygroscopicity is selected in the Heatless Desiccant Air Dryer, with uniform shape and size, high strength, high dew point, less dust, and long service life;
- The amount of regeneration gas can be adjusted according to the operation load demand of the equipment to achieve energy-saving effect;
- Special airflow diffusion device and automatic regeneration in the desiccant dryers, ensure the service life of desiccant;
- Programmable microcomputer controller, adsorption, regeneration working time can be adjusted to achieve your satisfactory dew point value.

Note: other special requirements are welcome to customize.

2.Operating Conditions

Inlet temperature:≤38°C

Ambient temperature:1-45°C

Standard Working Pressure:0.7Mpa

Power:AC220V/1P/50Hz/60Hz

Standard Configuration

PDP:-40°C

Adsorbent life:3 years

Valve with Stainless Steel Core

PLC Control

Optional Configuration

PDP:-70°C

Dew point display and energy saving module

Communication telex function

High temperature and high pressure intake

Galvanized or stainless steel pipe

Tower insulation



Suzhou Sumairui Gas System Co.,Ltd.



+8613812659092



dylan@sumairui.com



n2-nitrogengenerator.com

No 161,ZhongfengJie, Suzhou High technology district, Suzhou